

art. AR

CHILLED WATER STORAGE TANK

Product designed, manufactured and tested to the requirements of PED 97/23/EC (art.3.3).



DESCRIPTION:

Chilled water tanks are used for air conditioning installations in order to increase the thermal inertia and, for those installations without a low water-capacity, avoid that the chilling generator is continually working.

VERSION: vertical/horizontal

MAX WORKING PRESSURE: 6 bar

WARRANTY: 8 years

INSULATION: Fixed poliethylen – not subject to condensation.

External blue PVC or embossed aluminium

MAX WORKING TEMPERATURE: 40°C

CONNECTIONS:

- 1 - drain
- 2 - inlet
- 3 - outlet
- 4 - safety valve
- 5 - thermometre

MATERIAL:

Stainless steel

Model	u.m.	100	200	300	500	800	1000	1500	2000	2500	3000	4000	5000
Inner diameter	mm	450	500	600	650	800	800	950	1100	1100	1250	1400	1600
Total height	mm	970	1395	1440	1880	1870	2120	2385	2430	2730	2750	2810	2840



Advanced Technical Products Ltd

Unit 219, Block C, Blanchardstown Corporate Park 2, Ballycoolin, Dublin 15
 Tel: 01 885 3792, Email: info@atpireland.com, Web Site: www.atpireland.com